DEVALE



www.DEWALT.com

GUARANTEED TOUGH.



STEFAN KORTELAND IS...

GUARANTEED TOUGH.

Stefan understands power. Because it's his job to protect
The Netherlands from the brutal forces of the North Sea.
As an engineer on The Netherlands' largest flood barrier,
Stefan is responsible for maintaining the massive ocean
defence barrier protecting the low-lying population centres
from flooding. Often isolated from the mainland and suspended
above treacherous seas at the mercy of the elements,
mains electricity is not an option for Stefan's work.

Thankfully, he can rely on the DeWALT XR range, for the power of corded and the freedom of cordless. Stefan's toolbox is powered by the DeWALT XR FLEXVOLT battery, so he gets guaranteed performance wherever he needs to work.

Whether he's using his cordless SDS Hammer to drill anchor points into immense sea breaks, or maintaining the steel barrier doors with an impact wrench, Stefan can tackle every job with just one battery. Because the DEWALT XR FLEXVOLT is the only battery on the market that can switch from 54V to 18V.

Which means, after a long day on site, Stefan sleeps soundly, knowing that the barrier won't let him down. And neither will his tools.

"WE HAVE TO RELY ON CORDLESS."







54V XR FLEXVOLT 48MM 8KG SDS-MAX HAMMER DCH733

The hardest hitting cordless SDS-Max hammer on the market. The DEWALT 54V brushless motor and high capacity battery delivers 13.3 Joules of impact energy which offers high speed drilling with a maximum capacity of 48mm in solid concrete.

Despite its high performance, the DCH733 features class-leading vibration of 9.0m/s². This is thanks to Perform & Protect features including an Active Vibration Control handle and an Anti-rotation System which detects a loss of tool control and reacts instantly by cutting power.

* Bare unit DCH733N











SOMETIMES
BIGGER IS
BETTER







12AH XR FLEXVOLT BATTERY DCB548

Amp up your tools with the new 12Ah XR FLEXVOLT battery. The DCB548 will deliver the ultimate performance and runtime in the same size as our 9Ah XR FLEXVOLT battery. It also includes a built-in LED Fuel Gauge for instant charge status, and is compatible with all 18V XR tools and chargers.

NEW





54V XR FLEXVOLT 230MM CUT OFF SAW DCS 690

The latest addition to the XR FLEXVOLT range is the world's first 54V cordless cut off saw. The DCS690 delivers unrivalled cordless performance with a 54V brushless motor without the hassle of pull cord start up, petrol fumes or engine maintenance.

The 230mm blade offers an 83mm depth of cut with an adjustable dual feed water system to manage dust. Sealed battery hosing prevents dust and water ingress and a heavy load indicator helps the user cut with the optimised force.

-4	न्य हिन्स प्राप्त	
	DCS690X2*	
	Blade diameter	230 mm
	Bore size	22.2 mm
	Max. cutting capacity	83 mm
:t	No load speed	6600 rpm

* Bare unit DCS690N



SAW BLADES**

Designed to work with the XR FLEXVOLT DCS690 cordless cut off saw. Together they enable effortless cutting through concrete and masonry materials in wet or dry conditions.

EXTREME®

Weight

220
230 mm
22.23 mm
1.5 mm
10 mm



** Optimal working 6600rpm (DT40260) / 6650rpm (DT40255). 1 disc per pack.





54V XR FLEXWOLT HIGH TORQUE 190MM CIRCULAR SAW DGS 577

The cordless benchmark for high performance circular saws. Perfect for first fix applications offering performance of 2500W, an increase of 900W over the DCS575 with all the benefits of the XR FLEXVOLT cordless platform.

DCS577T2*

Blade diameter	190 mm
Max. cutting capacity 90°	65 mm
Max. cutting capacity 45°	50 mm
Bevel capacity	53°
Weight	5 kg

* Bare unit DCS577N. ** 200 x 50mm timber.

18V XR BRUSHLESS JIGSAW DCS334

The all new 18V XR Jigsaw now upgraded with a brushless motor for increased runtime and performance and compatible with over 100 tools in the range. The improved tool free blade change mechanism holds the blade more securely and keeps the blade squarer during use for the ultimate precision. Dual LED's and a built in dust blower keep the workpiece free from debris for the most accurate cut or switch to the included dual sided Airlock compatible extraction kit.

DCS334P2*

Max. cutting capacity (wood)	135 mm
Max. cutting capacity (aluminium)	25 mm
No load speed	3200 spm
Bevel capacity	47°

* Also available in a body grip version DCS335. Bare unit DCS334N

EXTREME RUNTIME CONTRACTOR SAW BLADE

Diamond shaped bore allows an efficient use of the blade in high torque applications.

	D140270	D1402/1
Blade diameter	190 mm	190 mm
Blade thickness	1 mm	1 mm
Kerf thickness	1.55 mm	1.55 mm
Kerf type	Thin	Thin
Number of teeth	24	36
Tooth geometry	ATB+R	ATB+R
Tooth angle	25°	25°



18V XR INFLATOR DCC018

The new DCC018 is a compact, high performance 18V inflator. As part of the XR 18V range, it is durable, easy to use and able to tackle big tasks thanks to its high pressure output.

DCC018N

Power source	12V / 18V / 230V
Maximum pressur	e 11 BAR
Unit of measure	BAR / kPA / PSI
Dual display	Target pressure and actual pressure. Bright, built in LED light
Gauge accuracy	+/- 0.15 BAR
Weight (4.0 Ah bat	ttery) 3.0 kg







Self-Levelling 360° Rotary Laser projects green bright beam either horizontally or vertically - up to 4 x brighter than Red Beam



Self-Levelling 360° Rotary Laser projects red bright beam either horizontally or vertically





	DCE079D1G - GREEN BEAM
Visibility range	76 m
Visibility with detector (supplied)	600 m
Compensation range	± 5°
IP rating	IP67
Pulse mode	Yes
Tripod mounting thread	5/8"
Drop test	2 m
Battery	2.0 Ah / 18V Lithium-ion

DCE074D1R - RED BEAM

- 1	
n	45 m
n	457 m
•	± 3°
7	IP54
s	Yes
"	5/8"
n	2 m
n	2.0 Ah / 18V Lithium-ion





DW099S

Accuracy per 10 m	+/- 2 mm	
Range	30 m	
Laser class	2	
Number of spots 1		
Battery measuren	2 x AAA - Up to 3000 nents (2500 Bluetooth)	



3 x AAA - Up to 3000 measurements (2500 Bluetooth)

Length, area, volume and height measurement. It also has addition and subtraction functions

Large colour display for good visibility in all working conditions

Integrated Bluetooth® unit allows data transfer to smart phones and tablets

DW03101

+/- 1.5 mm 100 m

3 x AAA - Up to 3000 measurements (2500 Bluetooth)





Take complete control of your own assets, or those of your team, via the Tool Connect App or web platform, and get ready for the jobsite of the future.



*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by DeWALT is under license.
*Google Play and the Google Play logo are trademarks of Google Inc. Apple, the Apple logo, iPhone, iPad, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.







IMPACT ENERGY



HAND / ARM VIBRATION



DRILLING DIAMETER



40MM 5KG SDS-MAX ROTARY HAMMER D25481K

Ergonomic and compact design maximises control and offers easy access to confined spaces. Rotation stop mode for chiseling and impact stop mode for rotary only drilling with dry diamond cores. Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 40mm in diameter and core drilling up to 100mm.



5KG SDS-MAX CHIPPING COMBINATION HAMMER D25810K

Delivering impact blows of 3150 directly to the bit (reduces stress to the tool). Soft rubber grip handles and low vibration improve user comfort lowering fatigue during extended use. Ideal for light demolition, surface prep or chiseling grooves and channel openings.

HOLLOW DRILL BIT SYSTEM

FAST, EFFECTIVE AND SAFER DRILLING FOR CONCRETE & MASONRY





FITMENTS

Both SDS-Max® and SDS-Plus® fitments available, matched to common rebar and anchor sizes.

AIRLOCK™ ADAPTOR

Connects directly to the DEWALT Airlock™ System forming a secure connection between bit and dust extractor.

HOLLOW SHAFT

Vacuum assisted dust extraction means less dust, reduced resistance, faster drilling, and less hole cleaning.

SDS-MAX® CAT. NO. **WORKING TOTAL** LENGTH MM MM LENGTH DT60230-0Z 400 600 16 DT60231-QZ 18 600 DT60232-QZ 20 400 600 DT60233-0Z 24 400 600 DT60234-QZ 28 400 600 DT60235-QZ 32 400 600

DRILL BIT RANGE



SDS-PLUS® HOLLOW DRILL BITS

Z GUTTER GARBIDE
For exact positioning of SDS-Pludrill bit diameters, delivering accurate starting and durability.



SDS-PLUS®

CAT. NO.	Ø MM	WORKING LENGTH MM	TOTAL LENGTH MM
DT60340-QZ	12	200	320
DT60341-QZ	14	250	370
DT60342-QZ	16	250	370
DT60343-QZ	18	250	370

38L CONSTRUCTION DUST EXTRACTOR DWV902M

This is a dedicated unit designed to work with the Airlock™ System to provide fast, safe and easy dust extraction for concrete and masonry spoil.

DWV902M

Power input 1400 W
Max. airflow 4080 I/min
Capacity 38 ltr
Wet / dry capacity 18.4 ltr
Weight 15 kg
Height 695 mm
Power take off rating 2200 W

M Classified to meet EU legislation


Innovative dual filter cleaning system maintains performance during tough construction applications

Constant suction power even with the finest concrete and wood dust

A filter is automatically cleaned every 30 seconds reducing filter clogging and delivering constant air

Built-in power take off socket allows power tool connection for automatic switching of the vacuum system







TOUGHSYSTEM® COOLER

DWST1-81333

New 25.5L ToughSystem® DS404 Cooler provides five days' ice retention, with IP65 rating for exceptional dust and water resistance. It features integrated can holders and bottle opener on the lid.

Fully compatible with all DeWALT ToughSystem® storage cases.






Dimensions	40.6 x 55 x 36.6 cm
Load capacity	40 kg
Ice retention	5 days

The new durable ToughSystem® two and three drawer modules deliver an extensive capacity and water / dust-resistant construction for the toughest outdoor jobsite conditions. Fully compatible with all DeWALT ToughSystem® storage cases.

DWST1-80123 / DWST1-81055

בפטו א-וופאע / צווטא-וופאע ש		
Dimensions	55.4 x 34 x 30.7 cm	
Load capacity - 2 drawer (DWST1-80123)	10 kg per drawer	
Load capacity - 3 drawer (DWST1-81055)	7 kg per drawer	









54V XR FLEXVOLT CHAINSAW DCM575X1

The high power 54V XR FLEXVOLT battery, combined with the brushless XR FLEXVOLT motor and the 40cm Oregon Bar and Chain allows the DCM575 chainsaw to cut through thick tree trunks easily and quickly†.

With the 54V XR FLEXVOLT motor, this chainsaw truly delivers unrivalled performance for a cordless chainsaw, without the hassle of pull cord start up, petrol fumes or engine maintenance. It is packed with features that make it quick to use and easy to maintain such as tool free chain tensioning and automatic oiling.

DCM575*

Runtime	Up to 65 (6 x 6 cuts (3.0 Ah battery)	
Chain speed		15 m/s	
Safety		Stops in under 1 second	
Chain replacement		Tool free bar fitment and chain tensioning	
Maintenance	3/10/	Auto oiling	

[†] Cutting 6 x 6 inch / 15 x 15 cm treated timber using 3.0 Ah battery. Bare unit DCM571N



54V XR FLEXVOLT BLOWER DCM572X1*

Extra powerful blower providing up to 400 CFM for extended durability, efficiency and power. Designed for comfort and control with features such as variable speed trigger with lock allowing the user to maintain their chosen power level without having to hold down the trigger.

54V XR FLEXVOLT STRING TRIMMER & BRUSH CUTTER DCM571*

Offering all the power of a petrol driven tool without the inconvenience of having to carry / mix fuel. The DCM571 String Trimmer / Brush Cutter also benefits from a 38cm swathe as well as brush cutter blade and adapter allowing it to be used for simple grass cutting or heavy duty clearing work.

25cm Triblade included for brush applications, plus adaptor kit also included.

* Bare unit DCM571N





X EXTREME X FLEX

DIAMOND CUT-OFF WHEEL

Designed to work with the XR FLEXVOLT™ DCS690 cordless cut-off saw. Together they enable effortless cutting through concrete and masonry materials.



DT40260-QZ	
Blade diameter	230 mm
Bore diameter	22.23 mm
Segment thickness	3 mm
Seament height	12 mm

X EXTREME X FLEX

CONTRACTOR SAW BLADE

For fast smooth cuts - optimised for cordless for more cuts per charge. Diamond shaped bore allows an efficient use of the blade in high torque applications.

	DT40270-QZ	DT40271-QZ
Blade diameter	190 mm	190 mm
Bore type	Diamond	Diamond
Kerf thickness	1.55 mm	1.55 mm
Kerf type	Thin	Thin
Number of teeth	24	36
Tooth geometry	ATB+R	ATB+R
Tooth angle	25°	25°





EXTREME® 2X



DEMOLITION SAW BLADE

With an aggressive, reinforced, shoulder design the DEWALT Demolition Saw Blade is ideal for cutting through wood with nails. C3 next generation carbide tips provide Extreme® durability with up to 2x Life.

Blade diameter	190 mm
Bore diameter	30 mm
Kerf thickness	1.6 mm
Teeth	24
Tooth direction	Anti-clockwise
Tooth geometry	ATB

18°

DT4395-QZ

Tooth angle



EXTREME*

SDS-PLUS® 2 CUTTER DRILL BITS

TOUGHCORE™* AND WEAR MARK* FOR ACCURATE MECHANICAL ANCHORS INSTALLATION

With the very latest TOUGHCORE™ technology, the new SDS-Plus® range provides maximum drilling performance with enhanced bit durability.

AVAILABLE FROM SEPTEMBER




TOUGHCORE™*

Tapered central core increases stability and durability and increases breakage resistance.

WEAR MARK*

Provides the reassurance that the holes you drill are the diameter you need - ideal for accurate mechanical anchors installation.



2-STAGE HELIX*

Effective dust removal improves drilling performance.

CARBIDE TIP

Solid two cutter head flanked by two cutting tips for fast and efficient drilling.



Compatible with SDS-Plus® hammer drills and ideal for fast drilling anchor and plug holes in concrete.

The range includes diameters

3mm to 24mm

and working

lengths of MADE IN GERMANY

50-540mm.





* Wear mark, TOUGHCORE™ and 2-stage helix are not available on all SKUs - see distributor listing for details.



EXTREME°

FLEXTORQ™ SETS AND CONNECTIBLE STORAGE SOLUTIONS

The DeWALT modular storage system is easy to use with interlocking cases to keep accessories and fixings safe and organised.

The range is fully compatible with the TSTAK™ system and is available with EXTREME® FlexTorq™ screwdriver bits.







A PLACE FOR EVERYTHING

SMALL BULK STORAGE

Keep all your 25mm driver bits and consumable accessories to hand

SMALL TOUGHCASE™

Stores Small Bulk Storage cases and bits with easy access bit holders. Unique locking system to secure multiple boxes together

TSTAK™ CADDY

Easy transportation of up to 4 small bulk storage boxes and 5 small ToughCase™ sets

TSTAK™ SYSTEM

A comprehensive range of options with drawer units, totes, customisable tool storage and more

TSTAK™ TROLLEY

Ideal for keeping your whole toolkit mobile



EXTREME

FLEXTORO SCREWDRIVER BITS

Optimised torsion zone, maximising bit life and turning force when used in extreme applications



DEWALT

PH2

LONGER LIFE*

EXTENDED

FLEXTORON

Full fit head eliminates wobble and screw head rounding Contoured area of the bit tip flexes with the torque of the impact driver

Flex optimised to transfer maximum torque through the screw and maximise life

Available in ToughCase™ dedicated sets in a range of sizes and head patterns to give you trouble free fixing and installation.

^{* 57}mm bits only, compared to standard range.





1000+ cuts per blade. 30X longer wheel life compared to bonded cut-off wheels*

ADVANCED DIAMOND TECHNOLOGY

Robust diamond edge segments prevents wear - the cutting depth of the blade is maintained delivering a consistent depth of cut

SAFETY

Strong, solid steel body greatly reduces the risk of breakage

LESS DUST RESIDUE

Less wear compared to bonded abrasives ensures less dust residue and odour





EXTREME® METAL CUT-OFF WHEELS

Specially designed to provide the ultimate in performance and durability. These wheels can be used with corded and cordless angle grinders as well as chop saws and gas saws on a wide range of metals.

Cat. No.	mm	mm Bore	Segment thickness mm	Qty.
DT40250-QZ	100	16	1.3	1
DT40251-QZ	115	22.23	1.3	1
DT40252-QZ	125	22.23	1.3	1
DT40253-QZ	150	22.23	1.3	1
DT40254-QZ	180	22.23	1.5	1
DT40255-QZ	230	22.23	1.5	1
DT40256-QZ	305	25.4	3.3	1
DT40257-QZ	355	25.4	3.3	1
DT40258-QZ	305	25.4	3.8	1
DT40259-QZ	355	25.4	3.8	1

* Average performance of Extreme® Metal versus 115 x 1mm (Aluminium Oxide) Bonded Abrasive Cutting Disc in 25mm Carbon Steel Tube.



UK

210 Bath Road, Slough, Berkshire SL1 3YD Telephone: 01753 567055

Fax: 01753 572112

www. **DEWALT**.com

The yellow and black colour scheme is used on DeWALT Power Tools and Accessories as a trademark. DeWALT reserves the right to change any deal at any time without notice. Deals available while stocks last.

Your DeWALT Dealer:

▲ TO SEE THE NOISE AND VIBRATION DATA VISIT WWW.DEWALT.CO.UK/SAFETY

Be the first to see product news and special offers from DeWALT. Register at MyDeWALT to be sent Onsite offers by email. Simply go to www.DeWALT.com/MyDeWALT



MY DEWALT.

an-ccc/6-

REGISTER AT